



## LE 2300 L-X Heavy Duty fuel and oil additive

### Product description

LE 2300 L-X® additive is a combination of carefully selected oils and chemical product. Modern, exclusive formulation reduces efficiently the wear of moving engine parts, keeps clean of internal parts of equipments, increases lifetime.

Protects engine and fuel system from corrosion.

### Applications

LE 2300 L-X® fuel and oil additive increases the power output of the engine, provides smoother engine performance, reduced fuel consumption and less maintenance.

Especially favourable for using as flashing agent (mix. 5%-10%) for central lubrication system of open gears.

The product can be used as chain or gun lubricant too.

Trucks, Buses, Automotive Fleets:	Add to fuel tank every 1600 km:	7,8	Add to crankcase every 1600 km:	47
<b>Farm, Construction, Heavy duty Equipment:</b>	Add every 50 hours:	7,8 ml/liter	Add to crankcase every 50 hours:	47 ml/liter
<b>Marine and Stationary Engines:</b>	Add every 75 hours:	6,2 ml/liter	Add to crankcase 75 hours:	47 ml/liter
<b>Bulk Fuel Storage Tanks:</b>		2,5 ml/liter		
<b>Outboard Motors, Mowers, Chain Saws:</b>		3,9 ml/liter		

### Product benefits

- Increases power output
- Reduces frictional wear
- Cleaner internal engine parts
- Extends engine life
- Reduces fuel consumption
- Less corrosion wear

### Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

In the original container under the recommended storage conditions: 48 months

Inflammability hazard: Grade III.

Recommended storage temperature: max. 40°C

# LUBRICATION ENGINEERS, Inc.®

Distributed by: MOL-LUB Ltd.

Technical service: H-1117 Budapest, Budafoki u. 59.

H-1986 Budapest, MOL Plc. Tel: +36-1-4640236 Fax: +36-1-4640304 E-mail: lubricants@mol.hu



**LE 2300 L-X Heavy Duty**  
*fuel and oil additive*

**Ordering information**

**SAP code and packaging:**

13005209 18,9l plastic pail

13006998 0,5l plastic bottle

**Order booking ( toll-free):**

Phone: +36-80/201-331 (between 07-16 h weekdays )

---

***LUBRICATION ENGINEERS, Inc.***<sup>®</sup>

Distributed by: MOL-LUB Ltd.

Technical service: H-1117 Budapest, Budafoki u. 59.

H-1986 Budapest, MOL Plc. Tel: +36-1-4640236 Fax: +36-1-4640304 E-mail: lubricants@mol.hu