

MOL Dynamic Moto 4T Scooter 10W-40

semi-synthetic four-stroke motorcycle motor oil



MOL Dynamic Moto 4T Scooter 10W-40 is a high performance partially synthetic engine oil having excellent engine protection capabilities, which withstands even the intensive thermal and mechanical shear stresses of state-of-art four-stroke motorcycles.

Application



- Four-stroke scooters and street motorbikes
- Dry and wet clutch motorbikes
- Motorcycles with or without a catalyst
- Air- or water-cooled motorcycles
- Motorcycles with separate or integrated gearboxes

Features and benefits

- Excellent shear stability
- Maintains its favourable properties for a long period even under heavy loads and shear stresses
- Optimal friction characteristics
- Correct torque transmission between clutch plates
- Outstanding detergent-dispersant properties
- Preserves engine cleanliness for a long period and prevents deposition of solid contaminants

Specifications and approvals

- Viscosity grade: SAE 10W-40
- API SN
- JASO MA2

Properties

Properties	Typical values
Density at 15°C [g/cm ³]	0,869
Kinematic viscosity at 40°C [mm ² /s]	98,3
Kinematic viscosity at 100 °C [mm ² /s]	14,7
Viscosity index	156
Pour point [°C]	-33
Flash point (Cleveland) [°C]	225
Base number (BN) [mg KOH/g]	6,4

The characteristics in table are typical values of the product and do not constitute a specification.

MOL Dynamic Moto 4T Scooter 10W-40

semi-synthetic four-stroke motorcycle motor oil



Storage and handling instructions

Store in the original container in dry, properly ventilated area.

Keep away from direct flame and other sources of ignition.

Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Engine oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects.

The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C