

MOL Dynamic Sprint 2T

two-stroke motor oil



MOL Dynamic Sprint 2T is a high performance pre-diluted two-stroke engine oil, which meets Japanese and European performance standards, produced from highly refined mineral base oils, using state-of-art additive system. It provides appropriate lubrication in mixture operated systems when the mixing ratio specified by the manufacturer in the engine manual is used (which is usually 1:50). The use of MOL Dynamic Sprint 2T is not recommended in mixture lubricated two-stroke engines working with fuels containing bio-ethanol (E85).

Application



Two-stroke gasoline engines with premix or oil injection (autolube) lubrication

Motorcycles with or without a catalyst

Modern two-stroke mopeds and scooters

Features and benefits

Contains a self-mixing additive

Entirely miscible with fuel

Outstanding cleaning effect

Prevents spark plug fouling and retards exhaustion system blockage

Low ash content

Reduces emission of smoke and harmful gases from the engine

Excellent wear protection

Long engine lifetime, even with durable heavy stress conditions

Specifications and approvals

JASO FD
API TC+
CEC TSC-3
ISO-L-EGD

Properties

Properties	Typical values
Density at 15°C [g/cm ³]	0,868
Kinematic viscosity at 40°C [mm ² /s]	65,5
Kinematic viscosity at 100 °C [mm ² /s]	8,7
Pour point [°C]	-33
Flash point (Cleveland) [°C]	92
Sulphated ash [mass %]	0,14

The characteristics in table are typical values of the product and do not constitute a specification.

MOL Dynamic Sprint 2T

two-stroke motor oil



Storage and handling instructions

Store in the original container in dry, properly ventilated area.

Keep away from direct flame and other sources of ignition.

Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Engine oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects.

The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C